

TOOLS | *Pneumatic impact wrenches*

Pneumatic impact wrenches enable the fast loosening and tightening of screws and nuts. The wrench has a powerful 6-disc motor. A protective rubber coating protects against external damage. Matching compressed air hoses are also available for hire.



Pneumatic impact wrenches

Compressed air in bar	Square tool holder in inches	Recommended screw size	Working torque in Nm	Fast torque (2 seconds) in Nm	Max. torque in Nm	Max. free speed in 1/min	Blows per minute	Connection thread (NFPT) in inches
6	1	M32	136-1,220	1,356	2,000	5,000	700	0.5
8.3	1	M32	163-1,464	1,356	2,400	5,250	830	0.5

Pneumatic impact wrenches

Min. hose diameter in mm	Sound level pressure/output (impact) (ISO15744)	Sound level pressure/output (free speed) (ISO15744)	Vibration emission/measurement uncertainty (ISO28927)	Tare weight in kg	Length of tool in mm	Länge des Werkzeugs in mm
13	99.8/110.8 dB (A)	103.4/114.4 dB (A)	8.0/1.2 m/s ²	11.2	360	360
13	99.8/110.8 dB (A)	103.4/114.4 dB (A)	8.0/1.2 m/s ²	11.2	360	360